



Shelter Technology, Engineering, Fabrication Directorate

Fabric Structures Team Technology Update

Jean Hampel
Team Leader
Fabric Structures Team
Army Natick Soldier RD&E Center
November 2011



Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE NOV 2011		2. REPORT TYPE		3. DATES COVERED 00-00-2011 to 00-00-2011	
4. TITLE AND SUBTITLE Fabric Structures Team Technology Update				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) US Army Research, Development and Engineering Command (RDECOM),US Army Natick Soldier RD&E Center,Natick,MA,01760				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES 7th Bi-Annual DOD JOCOTAS Meeting with Rigid & Soft Wall Shelter Industry & Indoor & Outdoor Exhibition, 1-3 Nov 2011, Panama City Beach, FL					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 18	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			



Fabric Structures Team Overview



FST Goal: Mature technologies for fabric shelter systems providing increased protection, improved habitability, and reduced logistics burden.

Technologies:

Advanced Fabric Structures including Airbeam Shelters :

Maintenance Shelters

Mobile Warehouses

Large Command Posts

CB Medical

Backpackable

Insulation & energy

Insulation

Radiant Floor Heating

Collective Protection – CB Defense:

Overpressure/Negative Pressure Shelters


CB Fabrics

Reactive Airlocks

Self-Decontaminating Fabrics

The Team:

- Jean Hampel - Team Leader, Mechanical Engineer
- Tom Larkham - Equipment Specialist
- Kristian Donahue - Chemical Engineer
- Robin Szczuka – Chemical Engineer
- Julia McAdams – Chemical Engineer
- Liz Swisher – Electrical Engineer
- Chris Aall – Mechanical Engineer
- Clinton McAdams – Mechanical Engineer
- Allyson Stoye – Chemical Engineer
- Stephanie Enos - Admin support



UNCLASSIFIED



- Provides Rapid, Lightweight, Durable Deployment
- Technology transitioned to Force Provider (HDT-Vertigo, Inc.) and Chemically and Biologically Protected Shelter (Federal Fabrics-Fibers, Inc.)
- Airbeam backpackable shelters – Nemo, Inc.



UNCLASSIFIED



40 Foot Wide Airbeam Shelter DLA Distribution Warehouse



- Six, 44" wide, 100' long shelters completed in March for Defense Logistics Agency (DLA) customer
- 10-man DLA crew trained at in deployment and operation of shelter
- DLA deployed shelters overseas



UNCLASSIFIED



Aviation Inflatable Maintenance Shelter



UNCLASSIFIED



Single Skin Chem/Bio Protected Airbeam Shelter with Inflatable Bump-Thru Airlock



- Based off the air-supported TEMPER design originally built for AMED through Force Provider (640 sq ft with a 20 ft long airlock)
- The entire airlock is made of textiles and can be completely deflated and rolled up into the shelter for storage/transport. All rigid frame and door components have been replaced with inflatable technologies (small-scale airbeams/inflatable bump-thru door)
- Can be deployed and operating as a ColPro Shelter in less than 30 minutes with 4 personnel
- Shelter fabric is a certified ColPro material made by Bondcoat
- All connections sealed using 2 Track MaxiGrip, creating an air tight seal for over pressuring and allowing for compatibility with current A2S col pro liners
- Sponsor: Army Medical Materiel Development Activity (USAMMDA)



UNCLASSIFIED



Large Command Post Airbeam Shelter NSRDEC Deployment – Sept 2011



UNCLASSIFIED

Airbeam & Frame Backpackable Tents



- Primary Objective - high performance backpackable tents with reduced weight and cube
- Congressionally directed program with Nemo, Inc., Nashua, NH
- Designs include novel inflatable airbeam technology and tensioned fabric/pole configurations



UNCLASSIFIED



NEMO Tent Evaluation at FOB Kunduz, Afghanistan, 10th Mountain Division



NOTE: Pic Below from MC SERDP Brief




UNCLASSIFIED

10-Man Isopod



MAGBAG – connects to vehicle undercarriage



8-Man Astro



UNCLASSIFIED

Goal: In collaboration with the Marine Corps, develop a test standard by which condensation build-up or mitigation can be quantified in small combat shelters

- Several 4- and 10-man shelters were deployed in the NSRDEC climatic chamber under a variety of temperature and humidity conditions.
- Warm, moist water vapor was introduced into the shelters to simulate human water-vapor exhalation at rest. Heaters were placed into the shelters to mimic body heat.
- Based on results, modifications and retesting, a new Test Standard was written: TOP 10-2-176 Condensation Testing





Airbeam Shelter with a Prototype Non-woven Insulation Liner



Non-Woven Composite
Fibrous Batting



Manufacturing Quilt Lines of
Current Prototype Liner System

Purpose:



- To develop an improved manufacturing process for a non-woven composite, insulation liner to be used in expedient soft wall shelters. Manufacturing improvements will increase thermal performance and likelihood of transition while decreasing product cost and weight.

Product(s):

- An improved manufacturing process for non-woven insulation tent liners shown through prototyping and pilot demonstration.
- Three or more 12" x 12" hand samples of non-woven composite liner fabricated with improved manufacturing techniques. These samples will be used for evaluation towards a new manufacturing process.
- Hand sample test results regarding thermal performance, weight, tear strength, flame resistance, etc.
- Demonstration of enhanced manufacturing capability through two full-scale prototype tent liners – one for a standard 32' TEMPER and one for an air-supported tent.
- System level test results providing weights, pack volume, overall system R value (thermal performance).
- A final test report documenting the efforts under this project, test methods used, and overall benefits achieved.

Payoff:

- Enhanced non-woven composite tent liners will provide improved thermal performance in highly-agile soft wall shelters resulting in less fuel consumption for expeditionary operations
- Soldiers will experience an higher quality of life due to better climate control, and enhanced ease of insulated shelter set-up



Purpose:


- To reduce energy and fuel usage of Army base camps by providing an expeditionary, light-weight, and durable shelter insulation system based off multi-layer, cellular insulation technology. Ideally, the resulting system will transport flat and expand into a robust, flame resistant, honeycomb construction that maximizes thermal efficiency when deployed.

Product:

- Highly energy efficient shelters with minimal impact on pack size and weight
- Two full-scale prototypes suitable for installation in existing military shelters (Air-supported TEMPER, and framed TEMPER), potentially containing manifold inflation systems for quick deployment
- Affordable manufacturing processes to deliver large width insulation panels for shelter use
- Test data indicating energy saving benefits as well as performance with regard standard military specifications such as durability and flame resistance

Payoff:

- Lessening fuel requirements results in a reduction of fuel convoys directly reducing associated soldier casualties
- Reduced Convoy Protection missions increase Warfighter availability for Counter Insurgency Operations.
- Reduced fuel use will increase funding available for Warfighter protective and offensive equipment
- Soldiers will experience a higher quality of life due to better climate control improving cognitive performance.
- Planned transition to PM Force Projection, PM Force Sustainment Systems, Force Provider




Heat Distribution Comparison
Forced Hot Air vs. Radiant Floor
Heating



Radiant Floor Heating Prototype



Electric and Hydronic Radiant
Floor Heating Systems



Thermal Imaging of Radiant
Floor Heating Prototype

Purpose: To reduce the energy required to power shelter heating systems which would reduce the logistical burden of fuel supply. The effort focuses on the design and development of a radiant floor heating system that would efficiently heat an airbeam shelter in cold weather climates, either replacing or in addition to current Environmental Control Units. Background research and technology downselect comparing electric or hydronic (liquid) systems.

Results/Products:

- Design and manufacturing process that is financially feasible and proficient.
- Energy Efficient radiant floor heating system prototype(s) that are lightweight, deployable, portable and durable.
- Possible continued testing of previously tested electric radiant floor heating prototype.

Payoff:

- Reduced fuel transport requirements due to 25% energy reduction.
- 100% silent heating system.
- Increased soldier comfort levels by eliminating hot spots created by forced hot air heating systems.
- Transition capabilities to multiple areas of the military; potential for transition to Product Manager – Force Sustainment Systems (PM-FSS) and Force Provider, Future Medical Shelter System and Joint Expeditionary Collective Protection

MANTECH: High Performance Chemical/Biological Agent Resistant Shelter Fabric



Purpose:

- ***Provide Chemical, Biological, Radiological and Nuclear (CBRN) protection at a low mass, low cost in high volume for shelter & airlock applications***

Results:

- ***High volume CBRN laminate production demonstration at target cost and mass***
- ***Multiple 600 sq ft structures with airlock meeting Joint Expeditionary Collective Protection (JECF) requirements***


Payoff:

- ***Lower cost and reduce logistics burden to achieve CBRN collective protection; warfighter protection & agility improved***
- ***Transition to procurement at lower mass for JECF in FY11 for JPO at TRL6***
- ***Transitions at lower mass and lower cost FY12 at Aberdeen Proving Ground for TOP-10-2-175 at TRL7***





Next Generation Airlocks for Col Pro Applications

**“Zero Volume”
Concept**




- New airlock technology concepts that are lightweight, compact, easily deployed, reduced volume and incorporate self-decontaminating textiles.
- Full-scale bio-simulant test apparatus and procedure developed
- Testing of prototypes ongoing

**Inflatable Airbeam
Concept**



UNCLASSIFIED



Goal: Reduce nosocomial infections in fabric shelters through the incorporation of reactive fabrics into shelter interiors.



New emerging textiles with the capability to neutralize common battlefield microbes in addition to chemical/biological warfare agents :

Warwick Mills, Inc:



- Chloramine based chemistry with hydantoin/siloxane attachment
- Advancements in textiles allow up to a 6000ppm load
- 3-log kill time in <1 hour on Bacillus Subtilis (Anthrax surrogate)
- Demonstrated reactive textile in developmental airlock

Crosslink, Inc:

- A reactive, electrochemical polymer coating system capable
- of generating H_2O_2 to detoxify chemical and biological warfare
- agents was developed and tested.
- Two configurations of this system were fabricated by
- screen-printing method on general purpose shelter fabric, as well as on tent liner fabrics.
- Demonstrated efficacy with numerous biological and chemical agents

Ventana Research Corp.

- Light-activated, reactive photocatalytic coatings that generate & reversibly store singlet oxygen (1O_2), a mild oxidant
 - Rapidly disinfects surfaces exposed to microbiological pathogens & toxic industrial chemicals
 - Demonstrated technology with shelter prototype





NSRDEC Participation in NASA's Desert Research and Technology Studies (D-RaTS)



- On 8 August 2011, an Interagency Agreement (IA) was established between the National Aeronautics and Space Administration's Johnson Space Center (NASA-JSC) and the Army Natick Soldier Research Development and Engineering Center (NSRDEC)
- The IA enables NSRDEC and NASA to leverage and collaborate on advancing technologies related to life support and remote basing.
- From 22 August – 14 September 2011, NSRDEC and industry partner HDT, Inc. participated in NASA's Desert Research and Technology Studies (D-RaTS) in Arizona providing three airbeam shelters, a rigid/fabric hybrid shelter and energy saving accessories such as solar shades and new shelter insulations.
- NASA used these shelters for their test command center and to house their space exploration vehicles. NSRDEC instrumented two airbeam shelters and conduct testing of three new shelter insulations to establish energy savings.
- The next step is to broaden the IA to establish an RDECOM-NASA IA



UNCLASSIFIED

